

This listing of claims is to replace all previous listing of claims.

Claims 1-21 (Canceled)

22. (Currently Amended) A fluorescence correlation spectroscopy module arrayed in an optical connection of a microscope comprising:

a support body;

a coupling connection disposed ~~within~~ coupled to said support body;

a pinhole array comprising ~~at least one~~ at least one pinhole disposed ~~within~~ coupled to said support body;

* ~~at least one~~ at least one detector ~~coupled to~~ coupled to said support body;

a lens array comprising ~~at least one lens~~ at least one lens ~~coupled to said support body, and positioned between said at least one pinhole in said pinhole array and at least one of said plurality of detectors~~ coupled to said support body, and positioned between said at least one pinhole in said pinhole array and at least one of said plurality of detectors ~~for focusing an emission light~~ for focusing an emission light

passing through said pinhole and onto said at least one detector;
and

a fiber optic waveguide disposed within said ~~support body~~
coupling connection for coupling in a stimulating light.

a plurality of dichroic beam splitters comprising a first
dichroic beam splitter and at least a second dichroic beam
splitter coupled to said support body in a beam path and wherein
at least one pinhole from said pinhole array is disposed between
said first dichroic beam splitter and said at least a second
dichroic beam splitter for focusing the beam between said first
and said at least a second dichroic beam splitters.

23. (Currently amended) The module as in claim 22, wherein
said coupling the optical connection of the microscope is an
optical inlet.

24. (Currently amended) The module as in claim 22, wherein
said coupling the optical connection of the microscope is an
optical outlet.

25. (Original) The module according to claim 22, further
comprising a collimator for generating a parallel light beam that

is disposed within said support body in a beam path after said coupling connection.

26. (Canceled)

27. (Canceled)

28. (Currently Amended) The module as in claim 272 , further comprising a common at least one receptacle holder removably inserted within said support body, wherein said at least one filter from said filter array and at least one dichroic beam splitter from said plurality of dichroic beam splitters form an optical unit that is are set in said common at least one receptacle holder.

29. (Canceled)

30. (Canceled)

31. (Currently Amended) The module as in claim 29 28, wherein said at least one optical unit further comprises at least one mirror.

32. (Currently Amended) The module as in claim 29 28.

further comprising at least one additional receptacle holder which is removably inserted into said support body and for receiving said at least one mirror, wherein said at least one optical unit is removably insertable arrayed within a said at least one receptacle holder that is removably inserted into said support body.

33. (Canceled)

34. (Canceled)

35. (Currently Amended) The module as in claim 22, further comprising wherein said at least one receptacle holder is removably disposed within said support body and wherein said at least one receptacle holder comprises shaped surfaces, and said support body has cavities having complementary shaped surfaces arrayed and fixed in a beam path in said support body.

36. (Previously Amended) The module as in claim 22, wherein said support body is made in one piece from a metallic material and has a connection flange for attaching said support body to the connection of the microscope.

37. (Currently Amended) The module as in claim 22 28.

~~further comprising a wherein said at least one receptacle holder has angled lateral surfaces and wherein said support body has a series of cavities for receiving said at least one receptacle holder, wherein said cavities have complementary angled lateral surfaces to accommodate the reception of align said optical unit in said at least one receptacle holder along the beam path.~~

38. (Currently Amended) The module as in claim 37, further comprising ~~further comprising a filter array comprising at least one filter and at least one additional filter from said filter array wherein said at least one filter and said at least one additional filter are frequency selective filters and are coupled to said support housing at least two frequency selective filter devices disposed within said receptacle holders.~~

39. (Previously Amended) The module as in claim 22, further comprising a collimator disposed within said support body and which is tuned to a numerical aperture of said fiber optic waveguide.

40. (Currently Amended) The module as in claim 39, further comprising ~~wherein said at least one filter is formed as a~~ frequency selective devices which choose different spectrum ranges of a set of emission wavelengths.

-6-

41. (Canceled)

42. (Currently Amended) A fluorescence correlation spectroscopy module arrayed in an optical connection of a microscope comprising:

a support body having a plurality of cavities aligned along a beam path;

a coupling connection disposed within coupled to said support body;

a pinhole array comprising one pinhole disposed within said support body;

a fiber optic waveguide disposed within said support body coupling connection for coupling in stimulated light along said beam path; and

a plurality of removable receptacle holders (15) removably inserted into each of said plurality of cavities in said support body (4) wherein each of said plurality of removable receptacle holders (15) have shaped centering surfaces for centering each of said plurality of removable receptacle holders (15) in each of

said plurality of cavities; and

a plurality of optical components comprising at least one filter and at least one beam splitter with each of said plurality of optical components being disposed in each of said plurality of removable receptacle holders, said plurality of beam splitters for confocal division of an incoming beam path and an outgoing beam path, whereby outgoing and incoming light is passing passes through each of said plurality of said beam splitters, or is reflected by each of said plurality of beam splitters while being focused.

43. (Currently Amended) A fluorescence correlation spectroscopy module arrayed in an optical connection of a microscope comprising:

a support body having a plurality of cavities aligned along a beam path;

a coupling connection ~~disposed within~~ coupled to said support body;

a pinhole array comprising one pinhole disposed within said support body;

a fiber optic waveguide disposed within said support body for coupling in a stimulation light; and

a plurality of removable receptacle holders removably inserted into each of said plurality of cavities in said support body wherein each of said removable receptacle holders have shaped centering surfaces for centering each of said plurality of removable receptacle holders in each of said plurality of cavities;

a plurality of optical components comprising at least one filter and at least one beam splitter with each of said plurality of optical components being disposed in at least one of said plurality of removable receptacle holders, said plurality of beam splitters for confocal division of an incoming beam path and an outgoing beam path, whereby outgoing and incoming light is passing passes through each of said plurality of said beam splitters or is reflected by each of said plurality of beam splitters while being focused; and

at least one mirror disposed in at least one of said plurality of removable receptacle holders, wherein each of said plurality of optical components and said at least one mirror can be removed from said support body and inserted in a different

order in a different one of said plurality of cavities or rotated 180° and reinserted to allow rapid frequency selection for the beam of the associated beam path.

Please add the following Claim:

44. (New) A fluorescence correlation spectroscopy module arrayed in an optical connection of a microscope comprising:

- a) a support body;
- b) a coupling connection coupled to said support body;
- c) a pinhole array consisting of only one pinhole coupled to said support body;
- d) at least one detector coupled to said support body;
- e) a lens array coupled to said support body and positioned between said pinhole and said at least one detector, for focusing an emission light passing through said only one pinhole and onto said at least one detector; and
- f) a fiber optic waveguide disposed within said coupling

connection for coupling in a stimulation light wherein said only one pinhole is disposed only along the emission light and not along the stimulation light in the module; and

g) at least one beam splitter for dividing said stimulation light into a stimulation light beam path and an emission light beam path, wherein said beam splitter is positioned before said pinhole in said emission light beam path.

45. (New) The module as in claim 44, further comprising at least one additional lens coupled to said support body and positioned in said support body in said stimulation beam path between said fiber optic waveguide and said at least one beam splitter to produce a first focal point before said beam splitter and said at least one beam splitter produces a second focal point after said at least one beam splitter that is confocal with said first focal point.

46. (New) A fluorescence correlation spectroscopy module arrayed in an optical connection of a microscope comprising:

- a) a support body;
- b) a coupling connection coupled to said support body;

c) a pinhole array comprising only one pinhole coupled to said support body;

d) a fiber optic waveguide disposed within said coupling connection for transmitting a stimulation light; and

e) a beam splitter coupled to said support body in a position for confocal division of said stimulation beam path to produce an emission beam path wherein said emission beam path and said stimulation beam path pass through said beam splitter or are reflected by said beam splitter while respectively being focused in a focal point;

wherein a focal point of said emission light is after said beam splitter and a focal point of said stimulation light is before said beam splitter.

47. (New) A fluorescence correlation spectroscopy module arrayed in an optical connection of a microscope comprising:

a) a support body;

b) a coupling connection coupled to said support body;

c) a pinhole array comprising only one pinhole disposed within said support body;

d) a fiber optic waveguide attached to said coupling connection for coupling in a stimulation light; and

e) a beam splitter coupled to said support body and positioned in said support body for confocal division of a common beam path of said stimulation light and an emission light, wherein said stimulation light is focused through a focal point between said fiber optic waveguide and said beam splitter.

48. (New) The module as in claim 44, further comprising at least one additional detector, and at least one additional beam splitter, coupled to said support body along a path of said emission light behind said pinhole to decouple a first wavelength of said emission beam.

49. (New) The module as in claim 45, wherein said only one pinhole is positioned in said support body along said emission beam at said emission beam focal point.